## **Product Information Sheet**

without

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	LLLGAILD KLGOI	LATION (LO) 2013/20	ors with regard to energ	gy labelling of light		
Supplier's name	e or trade mark:	SIGOR				
Supplier's address: SIGOR Licht GmbH, Eichenhofer Weg 81, 42279 Wuppertal, DE						
Model identifie	r: 6147401					
Type of light so	urce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap	o-type	E27				
(or other electri	c interface)					
Mains or non-mains:		MLS	Connected light source (CLS):	No		
Colour-tuneable	e light source:	No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	Yes		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		7	Energy efficiency class	E		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	22002700		
On-mode power (P <sub>on</sub> ), expressed in W		7,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90		
Outer dimensions	Height Width	108 60	Spectral power distribution in the	See image in last page		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,458			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	1	Survival factor	0,90			
the lumen maintenance factor	0,70					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	0,9	Stroboscopic effect metric (SVM)	0,9			

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

