Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SIGOR

Supplier's address: SIGOR Licht GmbH, Eichenhofer Weg 81, 42279 Wuppertal, DE

Model identifier: 5142901

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS			
Light source cap-type	GU5,3					
(or other electric interface)						
Mains or non-mains:	NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	Yes			
Product parameters						

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
•.	mption in on- 000 h), rounded est integer	7	Energy efficiency class	G		
indicating if it i in a sphere (3	us flux (фuse), refers to the flux 60º), in a wide in a narrow cone	350 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode expressed in W	power (P _{on}),	6,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
for CLS, expre	ndby power (P _{net}) essed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	95		
Outer	Height	46	Spectral power	See image		
dimensions	Width	51	distribution in the	in last page		
without	Depth	51	1	Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	35			
		Chromaticity coordinates (x and y)	0,462			
Parameters for directional light sources:						
Peak luminous intensity (cd)	840	Beam angle in degrees, or the range of beam angles that can be set	36			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	55	Survival factor	0,90			
the lumen maintenance factor	0,70					

(a)'-' : not applicable;

(b)_{'-'} : not applicable;

