## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: SIGOR Licht GmbH, Eichenhofer Weg 81, 42279 Wuppertal, DE

Model identifier: 6125501

| Type of light source: | Type | of light | source: |
|-----------------------|------|----------|---------|
|-----------------------|------|----------|---------|

| Lighting technology used:     | LED | Non-directional or directional: | NDLS |  |
|-------------------------------|-----|---------------------------------|------|--|
| Light source cap-type         | E27 |                                 |      |  |
| (or other electric interface) |     |                                 |      |  |
| Mains or non-mains:           | MLS | Connected light source (CLS):   | No   |  |
| Colour-tuneable light source: | No  | Envelope:                       | -    |  |
| High luminance light source:  | No  |                                 |      |  |
| Anti-glare shield:            | No  | Dimmable:                       | Yes  |  |
|                               |     |                                 |      |  |

## **Product parameters**

| Product parameters                                |  |                         |  |              |  |  |
|---|--|-------------------------|--|--------------|--|--|
| Parameter   |  | Value                   | Parameter  | Value        |  |  |
| General product parameters:                       |  |                         |  |              |  |  |
| Energy consur<br>mode (kWh/10<br>up to the neare  | 00 h), rounded   | 4                       | Energy efficiency class  | G            |  |  |
| dicating if it refe<br>a sphere (360°)            | s flux (фuse), in-<br>ers to the flux in<br>, in a wide cone<br>arrow cone (90º) | 250 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 1 800        |  |  |
| On-mode pow<br>pressed in W                       | ver (P <sub>on</sub> ), ex-  | 4,0                     | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,00         |  |  |
| (P <sub>net</sub> ) for CLS, 6                    | candby power expressed in W the second dec-                                      | -                       | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 80           |  |  |
| Outer dimen-                                      | Height   | 185                     | Spectral power dis-  | See image    |  |  |
| sions without                                     | Width  | 32                      | tribution in the   | in last page |  |  |
| separate con-<br>trol gear, light-<br>ing control | Depth  | 32                      | range 250 nm to 800<br>nm, at full-load  |              |  |  |

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre)  |              |  |                |
|---|--------------|--|----------------|
| Claim of equivalent power <sup>(a)</sup>  | Yes          | If yes, equivalent power (W)           | 25             |
|   |              | Chromaticity coordinates (x and y)     | 0,549<br>0,408 |
| Parameters for LED and OLED li  | ght sources: |  |                |
| R9 colour rendering index value   | 0            | Survival factor                        | 0,90           |
| the lumen maintenance factor  | 0,70         |  |                |
| Parameters for LED and OLED mains light sources:  |              |  |                |
| displacement factor (cos φ1)  | 0,70         | Colour consistency in McAdam ellipses  | 6              |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. |              | If yes then replace-<br>ment claim (W) | -              |
| Flicker metric (Pst LM)   | 1,0          | Stroboscopic effect metric (SVM)       | 0,9            |

(a)'-': not applicable; (b)'-': not applicable;

